

## WHAT IS CLAIMED IS:

1. An RF data transfer system comprising:  
means for detecting repetitive RF interference which occurs during RF data transfer intervals; and

means, operative in response to periodicity and duration data obtained by said  
5 detecting means, for scheduling said RF data transfer to avoid said interference.

2. The system of claim 1 wherein said interference is repetitive RF interference.

3. The system of claim 1 wherein said interference is a radar signal.

4. The system of claim 1 wherein said scheduling means includes means for shifting  
a time sequence of said RF data transfer to avoid said interference.

5. The system of claim 4 wherein a modulation of said RF data transfer is changed  
to accommodate said time sequence shifting.

6. The system of claim 4 wherein a code rate of said RF data transfer is adjusted to  
accommodate said time sequence shifting.

7. The system of claim 1 wherein said scheduling means includes means for  
skipping at least one time slot in a sequence of time slots of said data transfer to avoid said  
interference.

8. The system of claim 7 wherein a modulation of said RF data transfer is changed  
to accommodate said time sequence shifting.



12. A method of reducing repetitive RF interference with RF transmissions, said method comprising the steps of:

calculating characteristics of RF interference within an RF band of interest to arrive at an interference profile of the periodicity and discrete durations of said interference, and

adjusting time sequences of desired RF transmissions to accommodate said interference profile.

13. The method of claim 12 wherein said calculating step further comprises the steps of:

detecting interference using a narrow band filter; and  
sweeping said filter across said band of interest.

14. The method of claim 12 wherein said desired RF transmissions occur in sequential repetitive time slots and wherein said adjusting step includes the step of eliminating at least one of said time slots for the duration of said interference.

15. The method of claim 14 wherein said desired RF transmissions are rescheduled for the duration of said interference.

16. The method of claim 15 wherein a modulation of said RF transmissions is changed to accommodate data in remaining ones of said time slots.

17. The method of claim 15 wherein a code rate of said RF data transfer is adjusted to accommodate remaining ones of said time slots.

18. The method of claim 12 wherein said RF interference is repetitive RF interference.

19. The method of claim 18 wherein said repetitive RF interference is a radar signal.

20. A method for detecting and mitigating interference with RF data transmissions in certain RF bands, said method comprising the steps of:

determining time periods of repetitive RF interference within an RF band of interest, using at least one antenna in electrical communication with at least one RF filter, to arrive at an interference profile of periodicity and duration of said interference; and

adjusting a time sequence of desired RF data transmissions to accommodate said interference profile, rescheduling transmissions to avoid said interference.

21. The method of claim 20 wherein a modulation of said RF data transfer is changed to accommodate adjustment of said time sequence.

22. The method of claim 20 wherein a code rate of said RF data transfer is adjusted to accommodate adjustment of said time sequence.

23. The method of claim 20 wherein said certain RF bands are unlicensed bands.

24. The method of claim 20 wherein said interference is a radar signal.

25. The method of claim 20 wherein said desired RF data transmissions occur in sequential repetitive time slots and wherein said adjusting step includes the step of eliminating at least one of said time slots for the duration of said interference.

26. The method of claim 2 wherein a modulation of said RF data transfer is changed to accommodate data in remaining ones of said time slots.

27. The method of claim 26 wherein a code rate of said RF data transfer is adjusted to accommodate remaining ones of said time slots.

